



VOLTAGE READINGS									
Item	Tube	Pin 1	Pin 2	Pin 3	Pin 4	Pin 5	Pin 6	Pin 7	Pin 8
V 1	66C7	0V..	85VDC	-10VDC	+8VDC	88VDC	0V	0V	0V
V 2	6V6GT	0V..	1	+5V	+5V	+5V	+5V	+5V	+5V
V 3	66C7	0V..	85VDC	+87VDC	+80VDC	+80VDC	+85VDC	+81.3VDC	+81.3VDC
V 4	6N1P	0V..	+80VDC	+80VDC	+80VDC	+80VDC	+80VDC	+81.3VDC	+81.3VDC
V 5	633ZG	0V..	1	308VAC	322VAC	305VAC	305VAC	305VDC	305VDC

300VAC 330VDC 305VAC

#### **• TAKEN IN MISCELLANEOUS ELECTIONS**

THE COOPERATION OF THE MANUFACTURER OF THIS EQUIPMENT MAKES IT POSSIBLE

#### 1. MEASURED FROM IRON 8 ON X

A PHOTOFAC T STANDARD NOTATION SCHEMATIC  
© Howard W. Smit & Co., Inc., 1950

1. DC Voltage measurements are at 20,000 ohms per volt; AC Voltages measured at 1,000 ohms per volt.
  2. Socket connections are shown as bottom views.
  3. Measured values are from socket pin to common negative.
  4. Line voltage maintained at 117 volts for voltage readings.
  5. Nominal tolerance on component values makes possible a variation of  $\pm 10\%$  in voltage and resistance readings.
  6. Volume control at maximum, no signal applied for voltage measurements.